Generated c-code

```
/* Automatically generated file. Do not edit.
 * Format:     ANSI C source code
 * Creator:    McStas <http://neutron.risoe.dk>
 * Instrument: My_Instrument.instr (My_Instrument)
 * Date:       Sat Apr  9 15:27:56 2005
 */

/* THOUSANDS of lines removed here.... */

  /* TRACE Component Source */
  SIG_MESSAGE("Source (Trace)");
  mcDEBUG_COMP("Source")
  mccoordschange(mcposrSource, mcrotrSource,
    &mcnlx, &mcnly, &mcnlz,
    &mcnlvx, &mcnlvy, &mcnlvz,
    &mcnlt, &mcnlsx, &mcnlsy);
  mcDEBUG_STATE(mcnlx, mcnly, mcnlz, mcnlvx, mcnlvy, mcnlvz,mcnlt,mcnlsx,mcnlsy, mcnlp)
#define x mcnlx
#define y mcnly
#define z mcnlz
#define vx mcnlvx
#define vy mcnlvy
#define vz mcnlvz
#define t mcnlt
#define s1 mcnlsx
#define s2 mcnlsy
#define p mcnlp
  STORE_NEUTRON(2,mcnlx, mcnly, mcnlz, mcnlvx,mcnlvy,mcnlvz,mcnlt,mcnlsx,mcnlsy, mcnlsz, mcnlp);
  mcScattered=0;
  mcNCounter[2]++;
#define mccompcurname Source
#define mccompcurindex 2
{   /* Declarations of SETTING parameters. */
MCNUM radius = mccSource_radius;
MCNUM dist = mccSource_dist;
MCNUM xw = mccSource_xw;
MCNUM yh = mccSource_yh;
MCNUM E0 = mccSource_E0;
MCNUM dE = mccSource_dE;
MCNUM Lambda0 = mccSource_Lambda0;
MCNUM dLambda = mccSource_dLambda;
MCNUM flux = mccSource_flux;
#line 58 "Source_simple.comp"
{
 double chi,E,Lambda,v,r, xf, yf, zf, dx, dy;

 t=0;
 z=0;

 chi=2*PI*randO1();                    /* Choose point on source */
 r=sqrt(randO1())*radius;              /* with uniform distribution. */
 x=r*cos(chi);
 y=r*sin(chi);

 randvec_target_rect(&xf, &yf, &rf, &pdir,
      0, 0, dist, xw, yh, ROT_A_CURRENT_COMP);
```

Written by mcstas!

McStas is a (pre)compiler!

Input is .comp and .instr files + runtime functions for e.g. random numbers

Output is a single c-file, which can be compiled using e.g. gcc.

Can take input arguments if needed.